



## TSE 20/40 Twin Screw Extruder Attachment


- 20mm Parallel
- Clam Shell Barrel
- Co-rotating
- Segmented Screw Elements



... where quality is measured.

# TSE 20/40 Clam-Shell Attachment

## Software



- **Graphic Interface**

- Alarms
- Temperature
- Pressure
- Torque
- Auxiliary Speeds

- **Protocol Storage**

- **Data Logging**

- Temperature
- Pressure
- RPM
- Torque
- Auxiliary Speeds



C.W. Brabender® laboratory

### C.W. Brabender® support

A modern applications laboratory is available for all customers and interested parties for trials with their own materials. All **C.W. Brabender®** measuring systems can be tested under ideal conditions. An experienced expert team will assist all tests.

Together we will find the optimal solution to meet your testing needs.

## Features

The basic steps of food extrusion can be perfectly realized with co-rotating twin screw extruders -- making modular co-rotating twin screw extruders the ideal companion for many extruded food products.

Profit from the harmonized, modular conception of screws and barrels for optimally realizing all processing steps (feeding, conveying, blending, dispersing, reacting, venting, pressure build-up). The system configuration of each model can easily be adapted to the individual processing task - anytime and at low cost.

Combine several processing steps within a continuously working extruder and use your C.W. Brabender® twin screw extruder as a modern in-line compounder.

Depending on the extruder size, the material to be tested, and the processing task, throughputs up to 20 kg/h can be reached. The flexibility and high performance of the TSE 20/40 twin

screw technology allows for optimum application adaptation to range from laboratory and small-scale production to include all processing tasks relevant to various food systems.

Extensive additional equipment like measuring and control units or metering systems (gravimetric, volumetric, liquid) as well as downstream equipment is available in order to create modular turn-key construction of complete extrusion lines.

The TSE 20/40 is available with barrel lengths of 20 or 40 D. Metering and/or venting ports are located at 10 D, 20 D, and 30 D with side feeding capabilities (12 D and 22 D).

Furthermore, the barrel of the TSE 20/40 is divided horizontally, and can be tilted open on both sides. Allowing visual assessment of individual processing steps. Ideally suited for Research and Development applications.

## Technical Data

Screw Diameter	Screw Length L/D	Flight Depth	Drive Power	Screw Speed (min <sup>-1</sup> )	Screw Torque	Operating Temperature
20 mm	24, 40	3.75 mm	variable *	150	2x40 Nm	400°C

\* Attachment for Intelli-Torque Plasti-Corder®



### Example of a TSE 20/40 screw design possibility



**C.W. Brabender® Instruments, Inc.**  
 50 E Wesley St., South Hackensack, NJ 07606  
 Phone: 201.343.8425 • Fax: 201.343.0608  
 foodsales@cwbrabender.com • www.cwbrabender.com

All trademarks are registered.  
 Subject to change of design and technical modification without notice.